

SUPERINTENDENT
Miki R. Inbod

Telecommunications Device for the Deaf (909) 357-5018

John

OVENS/RANGE							
		Vulcan	SG44	8	\$ -	\$ -	
2	Convection Oven, gas, single deck, solid state controls, electronic spark ignition, gentle bake (5) units @ \$5,000 each = \$25,000 (2) units @ \$5,000 each = \$10,000	Vulcan	SG4	2	\$ -	\$ -	
3	36" wide heavy duty gas range. Stainless steel front, plate ledge, front top ledge with pull-out condiment rails, sides, base, stub back and 6" adjustable legs. Stainless steel extra deep crumb tray. Total input 140,000 BTU/hr. Duty as burners with 5" high of the deck. 1 1/4" diameter front gas connection, capped. Total input 140,000 BTU/hr. Exterior Dimensions: 36 3/4" d x 36" w x 36" h (1) unit @ \$2,000 = \$2,000 (1) unit @ \$2,000 = \$2,000 Cord and plug). Oven measures 27" w x 27" d x 13" h. Standard oven thermostat adjusts from 150°F – 550°F. Convection oven adjusts from 175°F – 550°F and the optional finishing oven for standard ovens adjusts from 300°F – 650°F. Standard oven supplied with one rack, convection oven with two racks. Both ovens allow for three rack positions. Oven door is heavy duty with counter weight door hinges. 1 1/4" diameter front gas manifold and 1 1/4" rear gas connection, capped. Total input 140,000 BTU/hr. Exterior Dimensions: 36 3/4" d x 36" w x 36" h on 6" adjustable legs.	Vulcan	V4B36S-NAT V	1	\$ -	\$ -	
4	PowerPan™ Tilting Skillet, gas, 40-gallon capacity, bead blasted cooking surface, 10° tilt cooking feature, with easy manual hand tilt, spring-assisted cover with vent, gallon & liter markings, food strainer, stainless steel construction with open leg frame, 200,000 BTU, CE, NSF. Overall Dimensions: 49 7/8 in. L x 41 in. W x 39 in. H (with the cover closed) or 71 in. H (with the cover open). 120 V/60 Hz/1 ph, 1.4 A.	Cleveland	SGL40T1	3	\$ -	\$ -	
KETTLES							
5	Kettle, Tilting, Electric, 80 Gal, 2/3 steam jacketed, 208v/60/3-ph, 29.4kw, 81.7 amps, floor- mounted. Includes CHS80 spring assisted cover, TD2 2" Tangent draw-off valve with strainer, DPK28 double pantry faucet and bracket kit. Overall Dimensions: Left to Right: 48 1/2" Front to Back: 40 1/4" Height (to kettle lip): 47 7/16"	Cleveland	KEL80T	1	\$ -	\$ -	

REVISED UNIT PRICE SHEET

BID NO. 24/25-0013

BID ITEM #	EQUIPMENT DESCRIPTION	BRAND	MODEL	QTY	UNIT PRICE	EXTENDED PRICE	ESTIMATED DELIVERY	WARRANTY
6	Kettle, gas, tilting, 40-gallon capacity, 2/3 steam jacket design, floor mounted control console supports, stainless steel exterior finish, standard with flanged feet, 50 psi rating, electronic spark ignition, cover & draw-off optional, 140,000 BTU. 120 V/60 Hz/1 ph, 10 A. Overall Dimensions: 453/4 in. L x 421/2 in. W x 401/2 in. H (with the cover closed) or 71 in. H (with the cover open).	Cleveland	KGL40T	2	\$ -	\$ -		
7	Steamcraft® Gemini™ 10 Convection Steamer, pressureless, gas, 2 compartments with individual generators, (5) 12 x 20 x 2-1/2 pans/compartiment capacity, SureCook controls, easyTimer 90-minute timer with dial and LED digital readout in minutes and seconds, includes SureCook load compensating thermostat, manual cooking mode and descale indicator, left-hand hinged door, controls on right, 1 standard treated & tap water connection, stainless steel construction, 6" adjustable legs with flanged feet, 144,000 BTU total, 120 V/60 Hz/1 ph, 300W Overall dimensions: 24 in. W x 331/8 in. D x 651/2 in. H	Cleveland	24CGA10.2	3	\$ -	\$ -		
8	Convotherm Combi Oven/Steamer, gas, with steam generator, (6) 18" x 26" full size sheet pan or (12) 12" x 20" x 1" hotel pan capacity, 9" easyTouch control panel, 20 stages each & 399 cooking recipes storage, (4) cooking modes: hot air, steam, combi-steam & retherm, multi-point core temperature probe, five-speed auto reversing fan, includes (3) wire racks, anti-microbial hygienic door handle, pull-out spray hose, ConvoClean+ fully automatic hands-free cleaning system, stainless steel construction, 0.6kW, 120v/60/1-ph, 7.5 amps, 68,200 BTU,							

REVISED UNIT PRICE SHEET

BID NO. 24/25-0013

BID ITEM #	EQUIPMENT DESCRIPTION	BRAND	MODEL	QTY	UNIT PRICE	EXTENDED PRICE	ESTIMATED DELIVERY	WARRANTY
11	School Milk Cooler, forced air, 34"W x 33 5/8"D x 46 7/8"H, 13.59 cu. ft., single access, exterior digital thermometer, (8) 13" x 13" x 11" or (4) 19" x 13" x 11" case capacity, self latching doors/lids with safety bumpers, cylinder lock, wire floor racks, floor drain, electronic control, auto defrost, stainless steel interior & exterior, R290 Hydrocarbon refrigerant, 1/4 HP, cULus, UL EPH Classified, UL Sanitation, Made in USA, Self Contained refrigeration 115v/60/1 ph, 3.0 amps, cord with NEMA 5 15P, 6" Heavy duty casters, (2) with brakes, standard.	Bev Air	SMF34HC-1-S	8	\$ -	\$ -		
12	School Milk Cooler, forced air, 49"W, 33-1/2" D, 19.66 cu. ft., single access, exterior digital thermometer, (12) 13" x 13" x 11" or (8) 19" x 13" x 11" case capacity, stainless steel interior & exterior, R290 Hydrocarbon refrigerant, 1/4 HP, UL, cULus, UL EPH, NSF, MADE IN USA, 115 V/60 Hz/1 ph, 3 A, 1/4 HP. 6" Heavy duty casters, (2) with brakes. Overall							

REVISED UNIT PRICE SHEET

BID NO. 24/25-0013

BID ITEM #	EQUIPMENT DESCRIPTION	BRAND	MODEL	QTY	UNIT PRICE	EXTENDED PRICE	ESTIMATED DELIVERY	WARRANTY
---------------	-----------------------	-------	-------	-----	------------	-------------------	-----------------------	----------

17 Dealer's Choice Freezer, Reach-in, one-section, self-contained refrigeration, microprocessor control with LED display, stainless steel front, full-height solid door (hinged right), anodized aluminum sides & interior, (3) epoxy coated shelves (factory installed), LED interior lights, 6" high casters, eco-friendly, non-flammable R-448A refrigerant, unit can be programmed to operate at -10°F, 1/2 hp, cR f

o n _

REVISED UNIT PRICE SHEET

BID NO. 24/25-0013

BID ITEM #	EQUIPMENT DESCRIPTION	BRAND	MODEL	QTY	UNIT PRICE	EXTENDED PRICE	ESTIMATED DELIVERY	WARRANTY
-----------------------	------------------------------	--------------	--------------	------------	-------------------	---------------------------	-------------------------------	-----------------